

Stitching Machine Oil Lubrication Systems







FEATURES & BENEFITS

- Automatic lubrication provides the right amount of lubricant at the right time for optimum reliability.
- Reduce friction and wear and protect bearings, slides and chains.
- A precisely controlled discharge of oil is delivered to each point while the machine is in operation.
- Easily replace your existing systems and their hard to find spare parts and components.

Adding a Bijur Delimon lubrication system increases equipment life by decreasing wear on vital components. Automatic Lubrication systems safely and continuously supply lubricant while your machine is running.



For more information about this product, please contact us at (+1) 800-631-0168 or sales@bijurdelimon.com

SureFire II PDI Single-Line Systems for Oil & Fluid Grease

- Capable of handling oil (20 to 1500 cSt) and soft greases (NLGI 000, NLGI 00).
- Lubrication points can be easily added to or removed from a system.
- · Multiple voltage options:
 - Single Phase: 100/115VAC, 200/230VAC, 24VDC
 - · Three Phase: 230/480VAC
- ZEM injectors available in manifolds with 1, 2, 3 and 5 oulets.
- Metering volumes of the ZEM's can be easily changed by switching caps.







ZEM Injectors

SureFire II SLR Single-Line Systems for Oil


- · Capable of handling oil (20 to 1500 cSt).
- Used with resistance fittings that can service up to 100 lubrication points.
- Multiple voltage options:
 - Single Phase: 100/115VAC, 200/230VAC, 24VDC
 - · Three Phase: 230/480VAC
- Resistance fittings offered in eight different resistance levels that allow a ratio up to 1:128.



SureFire II with no Controller



Meter Units



WWW.BIJURDELIMON.COM 36717 · R0 · 03/17