

# Manual Grease Gun

## Lever & Pistol Type

### General

The tough high pressure cast iron head makes the manual grease gun unique in comparison to common pot metal or die cast heads. They have easy to maintain original pressure and delivery under the hardest working conditions. A variety of designs from our standard to professional series of grease guns are available.

### Lever Type

#### **Standard Series (Part #F1200)**

- + Heavy-duty cast iron head with port for optional filler nipple.
- + Curved outlet pipe and coupler with ball check and hardened jaws.
- + Heavy-duty knurled steel barrel with large threads for easy loading.
- + Heavy-duty barrel with large threads and O-ring seal.
- + Rugged baked enamel finish.
- + Locking follower rod, heavy-duty spring, heavy-duty beveled rubber follower, no conversion needed for various filling.

#### **Deluxe Series (Part #F1205)**

Has the same features as standard series (part #F1200), plus:

- + Filler nipple for three-way loading.
- + Vinyl handle grip.

#### **Professional Series (Part #F1210)**

Has the same features as deluxe series (part #F1205), plus:

- + Variables stroke cast iron head.
- + Air bleeder valve.
- + Removable valve checks for ease of maintenance.
- + Metallic baked finish.
- + Zinc-plated lever handle and linkage.

### Pistol Type

#### **Professional Series (Part #F1222)**

Has the same features as standard series (part #F1200), plus:

- + Removable valve checks for ease of maintenance.
- + Air bleeder valve.
- + Filler nipple for three-way loading.
- + Metallic baked finish.
- + Zinc-plated handle and linkage.
- + One-hand action for hard-to-reach fittings.
- + Vinyl handle grip.



Part #F1205

**BIJUR DELIMON INTERNATIONAL**

(919) 465 4448 LOCAL  
(800) 631 0168 TOLL-FREE  
(919) 465 0516 FAX

[WWW.BIJURDELIMON.COM](http://WWW.BIJURDELIMON.COM)

2100 Gateway Centre Blvd., Suite 109  
Morrisville, NC 27560

## Technical Data

Head Burst Pressure	17000 psi (1200 bar)
Counter Pressure	7100 psi
Delivery	0.1 oz/stroke
Cartridges	14 oz bulk grease
	16 oz bulk grease

## Installation

- Cartridge:** Remove the barrel and retract the plunger. Insert the cartridge and reattach the barrel; release the plunger and the gun is ready for use.
- Bulk fill (suction):** Remove the barrel. Retract the plunger with the end of the barrel submerged in the grease and lock it into place. Reattach the barrel, release the plunger and the gun is ready for use.
- Bulk fill (filler pump):** Clean and insert the filler nipple of the gun in the filler valve of the bulk pump and activate the filler pump.

## Maintenance

If grease gun does not work after filling, unscrew the barrel two or three turns (with the plunger released and spring tension on the grease) and release the air trapped in the barrel.

## How to Order

Name	Type	Description	Part #
Grease Gun	Lever	Standard series	F1200
		Deluxe series	F1205
		Professional series	F1210
	Pistol	Professional series	F1222

## Accessories

Name	Description	Part #
3 Jaw Narrow Coupler	1/8" NPT (F)	F1223
Buttonhead Coupler	Standard, 1/8" NPT (F)	F1226
	Giant, 1/8" NPT (F)	F1228
Wire Braided Hose	12" long, 1/8" NPT (M) both ends, 3000 psi working pressure, 12,000 psi burst pressure	F1260
	18" long, 1/8" NPT (M) both ends, 3000 psi working pressure, 12,000 psi burst pressure	F1262
Buttonhead Fittings	Standard, 1/8" NPT	F1290
	Standard, 1/4" NPT	F1291
	Giant, 1/4" NPT	F1292
	Giant, 3/8" NPT	F1293

### BIJUR DELIMON INTERNATIONAL

(919) 465 4448 LOCAL  
 (800) 631 0168 TOLL-FREE  
 (919) 465 0516 FAX

[WWW.BIJURDELIMON.COM](http://WWW.BIJURDELIMON.COM)

2100 Gateway Centre Blvd., Suite 109  
 Morrisville, NC 27560