

Industrial Lubrication Pump Accessories



- Portable carts and pump hoists available to assist in moving drums and pails.
- Drum heater blankets to help maintain grease pumpability in cold environments.
- Low level switch kits for 120/400 lb. drums.
- Full range of filters, regulators and lubricators to maintain clean and regulated air flow to pumps.
- Runaway pump valve to cut off pump operation in event of a ruptured line.

Adding a Bijur Delimon lubrication system increases equipment life by decreasing wear on vital components. Automatic lubrication systems safely and continuously supply lubricant while your machine is running.



For more information about this product, please contact us at (+1) 800-631-0168 or sales@bijurdelimon.com

PROVEN QUALITY, RELIABILITY AND ACCURACY.

Drum Heater Insulated Blankets

Model 37506 - Fits size 120 lb. drums (15 gal/57 liter)

Model 55286 - Fits size 400 lb. drums (55 gal/208 liter)

General Description

Drum heater blankets protect products by maintaining desired temperature through an evenly heated area. Includes an adjustable thermostatic controller that allows setting and managing the material temperatures.

Technical Data

Approx. Temp: 160°F +/- 10° (71°C +/- 5°)	Voltage: 120VAC
Model 37506	Model 55286
Wattage: 400 (+/-5%)	Wattage: 960 (+/-5%)
Amps: 3.33 (+/-5%)	Amps: 8.00 (+/-5%)



Low Level Switch Kit for 120/400lb. Drums

Model LC10243 - For 120 lb. drums (15 gal/57 liter)

Model LC11036 - For 400 lb. drums (55 gal/208 liter)

Notes: (1) Requires cover and follower plate - order separately.
(2) Customer/user to provide 15/16" hole in cover.
(3) Can be used with any MFG pump.

Runaway Pump Valve

Model 35647 - For 2-3 1/2" Air Motors

Model 35647-1 - For 4-6" Air Motors

General Description

This device is to terminate operation of a reciprocating type air motor in the event of a ruptured outlet hose or the pump runs out of media.

For compressed air use only.

Operating Pressure Range	20 - 175 psi (1.4 - 12 bar)
Temperature Range	0° to 180°F (-18° to 82°C)

Operation

The control valve senses an increased volume of air to the pump, beyond the preadjusted setting, and shuts off the air supply to the pump. The "runaway" condition may be caused by any of the following: 1) depleted pumping material, (2) a ruptured line on the outlet of the pump, (3) excessive cavitation in the material supply.

Installation

The valve should be installed in a filtered and regulated air line.

Upstream plumbing from the valve should be 1/4" minimum. Connect the female end of the hose to the outlet of the valve. Installing these items as illustrated is recommended. Use one valve for each pump.



Portable Carts - Trucks • Dollies • Bases

Model F1301

2 wheel dolly - for 35, 50 and 120 lb. drum.

Model F1302

Band type dolly for 35 lb. pail.

Model F1303

4 wheel cart - for 120 lb. drums. Similar to F1301.

Model F1304

Band type dolly for 120 lb. pail.

Model F1305

Heavy duty 3 wheel platform truck for 55 gallon drum. Swivel wheel with locking brake. Will hold drum & hose reel.

Model F1306


X-frame type dolly for 400 lb. drum.



Model F1304



Model F1302



Model F1301



Model F1305



Model F1306

Air Regulators and Gauges - Mounting Brackets

Model F976

1/2" regulator with 0-250 psi range and 2", 0-160 psi pressure gauge.

Model F973

Same as F976 except 3/8".

Model F980

Same as F976 except 3/4".



Filters

Model F982


3/4" filter

Model F978

1/2" filter

Model F975

3/8" filter



Lubricators

Model F981

3/4" lubricator

Model F977

1/2" lubricator

Model F974

3/8" lubricator



Air Regulators and Gauges - Mounting Brackets

Model F985

1/2" filter, regulator (0-250 psi) gauge (2", 0-160 psi), lubricator.

Model F984

Same as F985 except 3/8".

Model F986

Same as F985 except 3/4".

Model F989

Mount kit for combo units.

