

SMAC MAX Controller

Industrial Lubrication Systems



Operation

The SMAC-MAX Controller is a multi-purpose programmable controller used with industrial lubrication systems. Controller settings are saved whenever power is interrupted. Up to four operating modes can be selected which allows the controller to be used with various lubrication system designs. The controller is available in both 110 and 220 VAC service.

Features

- + Digital status display on front cover for easy programming
- + System monitoring capabilities
- + Data memory function initiated at power down
- + 0-99 second afterblow
- + Monitoring of low pressure switch
- + Remote reset/manual run
- + Compact design



SMAC-MAX Controller

Technical Data

Operating Voltage	110 VAC or 220 VAC (50/60 Hz)
IP Enclosure Rating	IP-55 (Liquid tight connector)
Fault Relay Contacts	30 W (220 VAC)
Ambient Temperature	-4°F to 131°F (-20°C to 55°C)
Vibration	2G
Switch Input	5V/20mA
Weight	4 lbs (1.8 kg)
Electrical Fuse	5 amp (5x20)

Controller Status LEDs

Power	Green
Lube Pump	Green
Line Spray	Green
Low Level	Red
Air Pressure Low	Red
Pause	Yellow
None Lit	No input power to controller

Installation

- + Mount the controller in a clean area with easy access for programming and visual checking.
- + Mount controller on a flat surface.

How to Order

Name	Description	Part #
SMAC-MAX Controller	Controller with liquid tight connector (110 VAC)	42012-5
	Controller with liquid tight connector (220 VAC)	42012-4

When ordering, specify by name, description and part number, e.g. SMAC-MAX Controller with liquid tight connector (110 VAC), Part #42012-5.


Accessories

Description	Part #
Replacement Fuse 5x20 5 amp	31076-2


BIJUR DELIMON INTERNATIONAL
 (919) 465 4448 LOCAL
 (800) 631 0168 TOLL-FREE
 (919) 465 0516 FAX
WWW.BIJURDELIMON.COM
 1 Copley Parkway, Suite 104
 Morrisville, NC 27560

Electrical Terminal Connections

Motor Driven Lubricators



Pneumatically-activated Lubricators



Connection #	Description
	Ground
1, 2	L1 (1) and L2 (2) 110 or 220/230 VAC power supply
3, 4	Motor or solenoid valve output (110 or 220/230 VAC)
5, 6	Air solenoid for spray system
7, 8	Input- cycle completion Mode 2 (pressure switch) Mode 3 (cycle switch)
9,10	Stop signal switch (close at switch stop)
11, 12	Monitoring air pressure switch (close at air pressure lost)
13, 14	Input- low level (closed at low level) Or Machine Count Input
COM, NO, NC	Fault switch (normally open contact rating 1 amp max), NO: COM/NO, NC: COM/NC

Legend

	Ground
	Power supply (110 or 220/230 VAC)
	AC motor
	AC solenoid
	Cycle switch or pressure switch
	Low level switch (closed at low level)
	Air pressure switch

Operation

Keys Description

With the controller energized:



- + Press keys **S** and **R** simultaneously and release to enter control mode.
- + The display panel will now show a fixed letter for the selected mode and a flashing number (1-4).
- + To select the required mode press the **▲** key.
- + Press the **S** key to advance to the next parameter of the selected mode.
- + Repeat steps 3 and 4 above using the **◀▶** key to move across the digits and the **▲** key to change the value of the selected flashing digit.
- + On completion, press the **R** key to save the data and initiate a lubrication cycle.

Manual Override

- + With the controller energized press the **R** key to initiate a lubrication cycle.

Program Review

- + To review the preset data, press the **S** key repeatedly with the controller energized.
- + To return to operating condition display, release **S** key or depress **S** key for 5 seconds.

Fault Alarm

- + In any alarm condition, e.g. low level, low pressure etc., the pump will not be able to operate and the alarm lamp will illuminate. The fault condition must be rectified to cancel the alarm and reactivate the system.

Operation Mode

Timer Control Mode (d 1)
Recommended for Systems without a Pressure Switch or Cycle Switch

Low level alarm function enabled*

In this mode, the lubricating system runs according to the preset run time and idle time.

Pressure Control Mode (d 2)
Recommended for Injector Systems

Pressure switch function enabled/ Low level alarm function enabled*

A pressure switch installed downstream from the pump functions as the key monitoring device for the entire system. Normally the system will build up sufficient pressure required to activate the pressure switch (normally open) in a predetermined period of time (called monitor time) once the pump starts. The user can adjust the monitor time to a setting greater than the time required to satisfy the pressure switch (normally 1.5 times greater). If the system fails to reach sufficient pressure during that time period an alarm signal will be displayed (EEPP appears on the digital readout). Possible causes for this type of alarm could be pump malfunction, broken supply line or crushed supply line prior to pressure switch. Lubrication intervals are adjustable from 1 to 9999 (seconds/minutes/hours). An adjustable run delay (1-99 seconds) following a pressure switch closure assures adequate pressure downstream from the pump.

Cycle Control Mode (d 3)
Recommended for Progressive systems


Cycle switch function enabled/ Low level alarm function enabled*

The cycle switch mounted on a progressive divider valve is the key monitoring device for the entire system. Normally when grease is being discharged from the outlets of the divider valve, a cycle pin engages with the switch, confirming a successful lubrication cycle. The controller can be programmed to allow for a predetermined number of cycle counts (1-999). Once the preset number of counts is obtained the controller will stop the pump and revert back to the idle time setting (1-9999 seconds/minutes/hours). If there is no activity from the cycle switch within a specified period of time (Monitor time: 1-999 seconds), an alarm signal will be displayed (EEcY appears on the digital readout). Possible causes for this type of alarm could be pump malfunction, divider valve malfunction, broken supply line or blocked supply line or feed line.

Pulse Control Mode (d 4)
Recommended for Pulse systems

Low level alarm function enabled*

This mode is designed for pulse systems where the pump doesn't run continuously, such as a pneumatically actuated piston pump. The controller can be programmed to initiate multiple on/off signals to a solenoid valve for frequent cycling of the pump.




* For lubricators fitted with low level switch

Operation Mode Cont.

Advanced Setup Mode

In Advanced Setup Mode, additional features may be set to suit special application requirements.

To enter Advance Setup Mode:



Fault Conditions:

- **"EEPP"**-Monitor time-out

(Mode d2 - Injectors) Pressure switch did not activate within monitor time.

- **"EEHP"**-Pressure switch failure

(Mode d2 - Injectors) Pressure switch was activate at the beginning of a lube cycle. Once customer fixes pressure switch - alarm will clear automatically.

- **"EECY"**-Monitor time-out

(Mode d3 - Progressive) Cycle switch did not activate within monitor time.

- **"EE"**-Internal memory failure

(Checked at power up) No recovery. Turn off power and try again. If problem persists, replace control.

- **"EELL"**-"Yellow LED" -Low Level

(Steady Yellow) Low lubricant level has been detected.

BIJUR DELIMON INTERNATIONAL
 (919) 465 4448 LOCAL
 (800) 631 0168 TOLL-FREE
 (919) 465 0516 FAX
WWW.BIJURDELIMON.COM
 1 Copley Parkway, Suite 104
 Morrisville, NC 27560

Dimensional Schematics

Measurements shown in millimeters.

