

Barrel Pump

26:1 Ratio

General

These air operated drum pumps can dispense a wide range of lubricants from oil up to an NLGI #2 grease. Available for 120 lb and 400 lb drums.

Features:

- Double-toggle balances pressure on air valve trip mechanism to prevent binding or stalling.
- Corrosion-resistant chrome finish on piston rods alleviates packing wear.
- All steel construction.



Technical Data

Sizes	120 lb. drum (16 gallon/57 liter)	400 lb. drum (55 gallon/200 liter)
Max Temp	160°F +/-10° (71°C +/-5°)	160°F +/-10° (71°C +/-5°)
Dimensions	38" OAL (96.5cm)	47-7/16" OAL (120.5cm)
Delivery	5.25 lb./min. (2.3 Kg.)	5.25 lb./min. (2.3 Kg.)
Max Output Pressure	5,200 PSI (359 bar)	5,200 PSI (359 bar)
Weight	34 lbs. (16kg)	44 lbs. (20kg)
Air Inlet Thread	1/4" NPTF	1/4" NPTF
Outlet Thread	3/8" NPTF	3/8" NPTF
Pump air motor	2-7/16"	2-7/16"
Max Air Pressure	200 psi (14 bar)	200 psi (14 bar)
Min Air Pressure	40 psi (2.75 bar)	40 psi (2.75 bar)

How To Order

Part #	Description	Drum Size
39739	Bare Pump	120 lb. drum (15 gallon/57 liter)
39740	Bare Pump	400 lb. drum (55 gallon/208 liter)
338371	Drum Cover	120 lb. drum (15 gallon/57 liter)
338163	Drum Cover	400 lb. drum (55 gallon/208 liter)
200225	Follower Plate	120 lb. drum (15 gallon/57 liter)
338911	Follower Plate	400 lb. drum (55 gallon/208 liter)
ADA10121B	Bung Adapter	

BIJUR DELIMON INTERNATIONAL

(919) 465 4448 LOCAL
 (800) 631 0168 TOLL-FREE
 (919) 465 0516 FAX

WWW.BIJURDELIMON.COM

2100 Gateway Centre Blvd., Suite 109
 Morrisville, NC 27560